

Product Description

Defoaming agent STA-0514 is a kind of excellent synergism defoam polymer without silicon, can retain and eliminate foam that generate by mechanical mixing and coating itself reaction so as to obtain smooth, flat coating film, is a very economical defoaming agent.

Typical Properties

Components	Solid content	Specified Gravity (g/cm ³)	Appearance	Solvent
polyacrylic ester	40%	0.89-0.95	Colorless Tranparent liquid	Aromatic hydrocarbon solvent

Features and advantages:

STA-0514 can inhibit the mixing of air, reduce the foam generation, and can help the foam release and crack, so as to achieve a better defoaming effect.

Have excellent defoaming effect for high powder content base coat, no impact with re-coating.

Have good solubility, suitable for matt top paint and color paint.

Application scope

suitable for Acrylic resin, nitropaints, UV curing paints , two components polyurethane, epoxy resin, alkyd resin, curing system paints, etc

Usage,

Recommended usage 0.2-3% of total fomulation, grinding before use is better.

Package:

25KG/barrel

Cautions:

Sealed and keep in cool space, do not contact with eye and skin directly, do not stain other products and container, please make a trial before put in production. Use before expired.

The data above are for experimental reference only and do not have any guarantee . Users should carry out test applicability according to their own conditions and requirements.

For any questions, please consult our technicians 0769-22364709 22364149 23037849 Fax: 22382985

Santol chemicals marketing headquarter address: Rm 606 Guojing Building, Nancheng CBD Headquarter base, Nancheng District, Dongguan City, Guangdong China