

Product Description

STA-6600N is a solvent-type defoaming agent, good at bubble suppressing and defoaming. It is suitable for solvent and solvent-free, ultraviolet curing system, especially for thick film of polyurethane have excellent defoaming effect, simultaneously is good for Spray shower screen, rolling coating and other painting methods to eliminate and inhibit bubbles.

Typical Properties

Components	effective content	Specified Gravity (g/cm ³)	Appearance	Solvent
Modified polysiloxane	1%	0.92-0.96	Colorless Transparent liquid	methyl isobutyl ketone; MIBK

Features and advantages:

Excellent solvent-type coating bubble suppression and defoaming agent have a good inhibition and elimination effect on the bubbles generated in manufacturing, blending and processing.

For dip paint, it's good effect to inhibit and eliminate bubble during processing.

Recommend for PU manual paint and non transparent epoxy paint.

Application scope

Suitable for solvent based paint and solvent free epoxy paint.

Usage,

Recommended usage 0.2-1% of total formulation.

Package:

25KG/barrel

Cautions:

Sealed and keep in cool space, do not contact with eye and skin directly, do not stain other products and container, please make a trial before put in production. Use before expired.

The data above are for experimental reference only and do not have any guarantee. Users should carry out test applicability according to their own conditions and requirements.

For any questions, please consult our technicians 0769-22364709 22364149 23037849 Fax: 22382985

Santol chemicals marketing headquarter address: Rm 606 Guojing Building, Nancheng CBD Headquarter base, Nancheng District, Dongguan City, Guangdong China